

Ribbon cable halogen-free



Schneid GesmbH | Gewerbering 16 | A-8054 | Graz/Pirka | Tel: +43 (316) 285022

Products, data sheets, documentation, MR12-SCHEMA-calculator: www.schneid.at

Ribbon cables halogen-free 10, 14, 18 and 44-pin

for SCHNEID modules and module controllers

Order number: 030.xxxxx

Order code: Flachbandkabel-halogenfrei-xxxxx

Overview:

Halogen-free ribbon cable for SCHNEID modules in different wire sizes.



Variants:

Ribbon cable for **heating circuit module HK06 & HK12**

HALOGEN FREE

10-pin version 800mm standard length

Order number: 030.16794

Order code: Flachbandkabel halogenfrei für HK-Module

Ribbon cable for **CM08/CM12 communication base**

HALOGEN FREE

14-pin version 800mm standard length

Order number: 030.16792

Order code: Flachbandkabel halogenfrei für CM08-BASIS

Ribbon cable for **AIN module MR08 / MR12**

HALOGEN FREE

18-pin version 800mm standard length

Order number: 030.16791

Order code: Flachbandkabel halogenfrei für AIN Modul MR08/12

Ribbon cable for **module controller MR08 / MR12**

HALOGEN FREE

44-pin version 500mm standard length

Order number: 030.16793

Order code: Flachbandkabel halogenfrei für MR08/MR12 Regler

Ribbon cable halogen-free

Scope of delivery:

According to the order of the individual components.

Technical specifications:

Intrastat Number:	8544.42.90.10
Country of origin	EU/AT
Height, width, depth (in mm)	17x800x7mm ribbon cable halogen-free for HK modules 10p / 800 23x800x7mm ribbon cable halogen-free for CM08-BASIS 14p / 800 27.5x800x7mm ribbon cable halogen-free for AIN module MR08 / 12 18p / 800 61x500x7mm ribbon cable halogen-free for MR08 / MR12 controller 44p / 500
Weight (in kg)	0.018kg flat ribbon cable halogen-free for HK modules 10p / 800 0.027kg flat cable halogen free for CM08-BASIS 14p / 800 0.034kg flat ribbon cable halogen-free for AIN module MR08 / 12 18p / 800 0.056kg ribbon cable halogen-free for MR08 / MR12 controller 44p / 500
Degree of protection	IP20
Ambient temperature	-40°C to +105°C
Connection type	IDC-socket
Coat color	grey
Outer jacket material	PVC
Cable type	Ribbon cable, tinned copper with gray PVC insulator
Rated current	500 mA